

SPECIFICATIONS

STYLE NAME: <b>CRAFTECH</b>	BACKING TYPE: <b>COMFORT BACK</b>
FINISH: <b>PU LACQUER</b>	AVAILABLE WIDTH: <b>13'2"</b>
PATTERN REPEAT: <b>REFER TO DESIGN CHART BELOW</b>	STANDARD ROLL LENGTH (TOLERANCES APPLY): <b>98 FT.</b>
NOMINAL WEAR LAYER THICKNESS: <b>10 MILS (0.25 MM)</b>	WEIGHT PER SQUARE YARD: <b>3.05 LBS/SQ. YD.</b>
NOMINAL PRODUCT THICKNESS: <b>100 GAUGE (2.5 MM)</b>	COUNTRY OF ORIGIN: <b>MANUFACTURED IN USA WITH GLOBAL COMPONENTS</b>

WARRANTIES

20 YEAR LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY

PERFORMANCE

ASTM F1303: <b>TYPE 1 GRADE 2 CLASS A</b>	AATCC 134 (STEP) ELECTROSTATIC: <b>0.1 K.V. OR LOWER</b>
<b>FLOORSCORE CERTIFIED</b>	ASTM C1028 SCOF: <b>DRY .72 WET .66</b>
CPSC-CH-C1001-09.3 PHTHALATES: <b>MEETS CPSIA GUIDE</b>	ASTM F970 STATIC LOAD: <b>PASS</b>
ASTM E648 CRITICAL RADIANT FLUX: <b>CLASS 1</b>	ASTM F137 FLEXIBILITY: <b>PASS 6 MM MANDREL</b>
ASTM E662 SMOKE DENSITY: <b>UNDER 450</b>	ASTM F925 CHEMICAL RESISTANCE:
ASTM F1515 LIGHT STABILITY <b>&lt; 8.0 DELTA E</b>	ASTM F1514 HEAT STABILITY DELTA E <b>&lt; 8.0: PASS</b>
ASTM F963 HEAVY METAL CONTENT ANALYSIS: <b>PASS</b>	ASTM D4060 ABRASION RESISTANCE: <b>10,000 CYCLES</b>
WATER PENETRATION IMPACT – 10,000 CYCLES: <b>PASS</b>	

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER WITH A MICROFIBER MOP.

INSTALLATION

END USE: <b>RESIDENTIAL</b>	SUITABLE GRADE LEVEL: <b>ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST</b>
INSTALLATION METHOD: <b>DIRECT GLUE DOWN / LOOSE LAY UP TO 25 SQ YD/225 SQ FT</b>	INSTALLATION SUNDRIES AS REQUIRED: <b>BEAUFLOOR 4N1 MULTIPURPOSE ADHESIVE, BEAUFLOOR CV SEAM SEALER OR COLD WELD</b>

DESIGN                      PART NUMBER                      PATTERN REPEAT                      PLANK/TILE SIZE

ARKOSE 696D	50053629	78.74" X 59.05"	10" W x 20" L
SODIUM 369L	50053631	39.37" X 59.10"	7.8" w x 59" L
CALCIUM 139L	50053630	78.74" X 59.05"	10" W x 20" L
FLINT 369M	50053633	39.37" X 59.05"	Multi plank size largest plank (9" W x59" L)
ZINC 369M	50053635	39.37"X 39.37"	13" W x 13" L
TONGSTEN 699D	50053632	39.37" X 59.10"	7.8" w x 59" L
PYRITE 156M	50053634	39.37" X 59.05"	Multi plank size largest plank (9" W x59" L)
LITHIUM 170L	50053636	39.37" X 39.37"	13" W x 13" L