

# 4220H

## 20 MELT FLOW ULTRA HIGH IMPACT COPOLYMER FOR INJECTION MOLDING

### Product Description and Applications:

Pinnacle Polymers Polypropylene 4220H is made via UNIPOL™ PP technology, which utilizes gas- phase fluidized bed reactors with a high activity catalyst system to ensure uniform physical properties and lot-to-lot consistency.

This product is intended for injection molding of flooring, automotive, appliance, lawn and garden products, and industrial applications. Provides an excellent base stock for compounding of filled and reinforced grades.

### Features:

The 4220H product provides:

- High impact and melt flow
- Superior balance of stiffness and impact strength
- Excellent color and processing stability
- UL Listed

It is characterized by its easy mold flow and high impact at both room and sub-ambient conditions.

Pinnacle’s 4220H polypropylene as marketed by Pinnacle Polymers Company, in natural, uncolored pellet form is covered under US FDA Food Contact Notification 864. As such, this polymer complies with the requirements of CFR Title 21 and can be used in contact with all food types under Conditions of Use A-H.

### Typical Properties

Property	Traditional Units	SI Units	ASTM Test
Melt Flow Rate	20 g/10 min.	20 g/10 min.	D1238 <sup>1</sup>
Density at 23°C	0.9 g/cm <sup>3</sup>	900 kg/m <sup>3</sup>	D1505
Shrinkage	0.013 in/in	0.013 mm/mm	D955
Heat Deflection Temperature at 0.455 MPa (66psi)	221°F	105°C	D648
Tensile yield strength, at 51 mm/min	3500 psi	24.2 MPa	D638 <sup>2</sup>
Flexural modulus (1% secant) at 1.27 mm/min	160,000 psi	1103 Mpa	D790A <sup>2</sup>
Yield Elongation	6%	6%	D638 <sup>2</sup>
Notched Izod Breaks at 73°F/23°C	100% No-breaks	100% No-breaks	D256 <sup>2</sup>
Notched Izod impact strength, at 73°F/23°C	≥10 ft-lb/in	≥534 J/m	D256 <sup>2</sup>
Gardner Impact strength at -22°F/-30°C	225 in-lb	24.8 J	D5420 <sup>3</sup>

<sup>1</sup>Condition L 230/2.16

<sup>2</sup>ASTM Type I specimen, 3.2 mm thick (injection molded per ASTM D4101-92a)

<sup>3</sup>Method G, Geometry GC

UNIPOL is a trademark of W. R. Grace and Co.

FDA and SDS documents are available on our website at: <http://www.pinnaclepolymers.com/datasds.php>

Technical data contained herein is furnished without fee or obligation, and is given and accepted at recipient’s sole risk. Since conditions of use may vary and are beyond our control. Pinnacle Polymers makes no representation about and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects, industrial hygiene requirements, or other matters associated with particular application of any product described herein. Pinnacle Polymers disclaims any warranty, expressed or implied, regarding the information contained herein, including the implied warranty of merchantability of fitness for a particular purpose. 010518