Ocean 12 V4.
Technical data.

BERRY ALLOC

11/2023

	contains	m²	ft²	weight
1 pack Ocean 12 V4	6 planks	1,47 m²	15.80 ft²	16 kg
1 pallet Ocean 12 V4	56 packs	82,23 m²	885.07 ft²	908 kg

hydro+

product specifications

Dimensions	1288 x 190 mm
Total thickness	12 mm
Bevels	4
Loc System	PentaLoc
Level of use according to European standard EN10874	23 heavy domestic use
	33 heavy commercial use
Residential warranty	lifetime
Commercial warranty	10 years

Warranty conditions on www.berryalloc.com.

composition

Surface layer	Direct laminated paper, impregnated with melamine resin.
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with hydro+ water repelling technology.
Backing	Direct laminated paper, impregnated with melamine resin.

test results

Abrasion resistance	EN13329	AC5 (IP ≥6000)
Impact resistance	EN13329	small ball: ≥ 70 mm - big ball: ≥ 1000 mm
Thickness swelling	ISO 24336	12% (requirement ≤ 15%)
Water resistance	ISO 4760	up to 24 hours
Fire resistance	EN13501-1	Cfl-S1
Formaldehyde emission	EN717-1	E1
Slip resistance	EN13893	DS
Density	EN323	900 kg/m³
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN16581	no damage (foot type 0)
Effect of a castor chair	EN425	no damage with type W wheels
Thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,12 m²K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com.

EN 14041
CE 23 DOP 170-DPLA23-1
UKCA 23 DOC UK 170-DPLA23-1
Berryalloc NV
Industrielaan 100
8930 Menen, Belgium
NB 1161
Laminate floor covering for use within building
www.berryalloc.com

PEFC
PEFC/07-31-229
PEFC Certified
laminate flooring from sustainably managed forests and controlled sources
www.pefc.be

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

23
33


laminate.

Ocean 12 V4.
Technical data.

BERRY ALLOC

11/2023

What is a laminate floor made of?



1. An **overlay** that determines the strength and resistance of your floor
2. A **decor paper** for the design
3. A **high-density fibreboard** (HDF) core
4. A **counterbalance** to stabilise and protect the HDF core
5. The **hydro+** water-repellent coating*

(*) Only available for our Ocean+ collections

laminate.